


Product Specifications

FlashLink® USB Reusable Data Logger with External Probe

Probe Measurement Range	-40°F to 185°F (-40°C to 85°C)
Probe Size: Penetration tip (20902)	0.14 in Dia x 3.98 in L (3.5mm Dia x 101mm L), 3.28 ft (1 m) Teflon cable
Blunt tip (20903)	0.15 in Dia x 0.98 in L (3.8mm Dia x 25mm L), 3.28 ft (1 m) Teflon cable
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	2 seconds typical for 3823 points
Programmable Alarm Levels	High & Low levels over entire range
Battery	3.6V Lithium/18 months
Dimensions/Body	1.575 in x 3.189 in x 0.575 in (40 mm x 81 mm x 13 mm)
Casing	PC/ABS plastic
Certification	CE Mark, NIST traceable, RoHS Compliant
Display	LCD, Red LED Alarm
Waterproof Rating	IP64 with silicon cap on
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH
System Requirements	Windows PC with current operating system, Adobe Reader
Programming	FlashLink Program Manager software or USB Program Manager software
Download Requirements	Direct USB connection
Patent No. 6,088,514	
	
DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system	



Blunt Tip

Models

Sharp Tip	20902
Blunt Tip	20903

- Single channel, external probe for product core temperature
- User Programmable: manual or automatic start, sample interval, alarm limits, data tags
- Large, easy to read LCD display
- Trip history statistics available on LCD
- NIST traceable and CE Mark
- USB Connection

SS 20902-X 20H1

