

Product Specifications

FlashLink. NOW CO₂ 4G/5G Real-Time In-Transit Logger

Temperature Range	-30°C to 70°C (-22°F to 158°F)
Temperature Accuracy	±0.5°C from -20°C to + 40°C (±0.9°F from -4°F to 104°F), ±1°C for other range
Resolution	0.1°C/°F / 0.1% CO ₂ / 1% RH
Humidity Range	5% to 95% RH
CO₂ Range	0-100 VOL%
CO₂ Accuracy	5-15% @ ±0.1% for other ±2%
Light Sensor Range	0 to 52000 lux
Light Detecton Accuracy	0.01 lux
Usage Type	Single-use
Data Capacity	Max 28800 Readings
Logging Interval	10 Min.
Data Upload Interval	90 Min.
Trip Duration	70 Day (based on logging and uploading intervals)
Cellular	Global LTE Cat-1 4G/5G network, with 2G Fallback
SIM	Internal Embedded (Global Data Roaming)
Power Source	Lithium-ion battery, meets UN38.3
Battery Shelf Life	12 months
Logger Dimensions	4.05in x 2.41in x 0.9in (103mm x 61.3mm x 23mm)
Weight	7 oz (200 grams)
Waterproof Rating	IP64
Certification	FCC, RoHS, NIST traceable temperature accuracy
PDF Report Backup	Micro USB to USB cable to download full trip PDF report



Model 22394

Next generation of global cellular communications real-time loggers with LCD using 4G/5G LTE/2G

Precision location accuracy using latest global cellular technology with Wi-Fi triangulation positioning

Monitors location, dual temperature, humidity, CO₂ level, light, and shock

Proactively manage shipment location and conditions to reduce the risk of product loss due temperature excursions

FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions

USB option to download PDF trip data should GSM network not be available.

Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 22394 24D1

